

NS推進管(継手性能JC)

[標準管]

(日本下水道協会規格)

呼び径	内径 D	厚さ T	長さ L	価 格			重 量
				1種50	2種50	1種70	
mm	mm	mm	mm	円	円	円	kg
800	800	80	2,430	別途見積	別途見積	別途見積	1,340
900	900	90	"				1,680
1,000	1,000	100	"				2,070
1,100	1,100	105	"				2,390
1,200	1,200	115	"				2,850
1,350	1,350	125	"				3,470
1,500	1,500	140	"				4,320
1,650	1,650	150	"				5,080
1,800	1,800	160	"				5,910
2,000	2,000	175	"				7,160
2,200	2,200	190	"				8,540
2,400	2,400	205	"				10,100
2,600	2,600	220	"				11,700
2,800	2,800	235	"				13,400
3,000	3,000	250	"				15,300

NS形推進管(継手性能JC)

[カラーなし管]

(日本下水道協会規格)

呼び径	内径 D	厚さ T	長さ L	価 格			重 量
				1種50	2種50	1種70	
mm	mm	mm	mm	円	円	円	kg
800	800	80	2,430	別途見積	別途見積	別途見積	1,300
900	900	90	"				1,640
1,000	1,000	100	"				2,030
1,100	1,100	105	"				2,340
1,200	1,200	115	"				2,800
1,350	1,350	125	"				3,400
1,500	1,500	140	"				4,240
1,650	1,650	150	"				4,990
1,800	1,800	160	"				5,810
2,000	2,000	175	"				7,050
2,200	2,200	190	"				8,420
2,400	2,400	205	"				9,990
2,600	2,600	220	"				11,500
2,800	2,800	235	"				13,200
3,000	3,000	250	"				15,100