

NS推進管 (継手性能JC)

[標準管]

(日本下水道協会規格)

呼び径	内径 D	厚さ T	長さ L	定 価			重 量
				1種50	2種50	1種70	
mm	mm	mm	mm	円	円	円	kg
800	800	80	2,430	120,200	139,600	135,000	1,340
900	900	90	〃	146,500	169,300	163,600	1,680
1,000	1,000	100	〃	177,400	207,100	197,900	2,070
1,100	1,100	105	〃	203,700	235,700	227,700	2,390
1,200	1,200	115	〃	241,400	281,400	270,000	2,850
1,350	1,350	125	〃	310,000	360,400	346,700	3,470
1,500	1,500	140	〃	369,500	431,400	414,200	4,320
1,650	1,650	150	〃	439,400	512,500	492,000	5,080
1,800	1,800	160	〃	504,500	589,200	566,300	5,910
2,000	2,000	175	〃	585,800	684,100	657,800	7,160
2,200	2,200	190	〃	691,100	807,700	775,700	8,540
2,400	2,400	205	〃	別途見積			10,100
2,600	2,600	220	〃				11,700
2,800	2,800	235	〃				13,400
3,000	3,000	250	〃				15,300

NS推進管 (継手性能JC)

[カラーなし管]

(日本下水道協会規格)

呼び径	内径 D	厚さ T	長さ L	定 価			重 量
				1種50	2種50	1種70	
mm	mm	mm	mm	円	円	円	kg
800	800	80	2,430	86,900	106,400	101,900	1,300
900	900	90	〃	108,300	131,200	125,400	1,640
1,000	1,000	100	〃	134,500	164,200	155,000	2,030
1,100	1,100	105	〃	156,000	188,000	180,000	2,340
1,200	1,200	115	〃	186,600	226,600	215,200	2,800
1,350	1,350	125	〃	230,100	280,400	266,700	3,400
1,500	1,500	140	〃	276,500	338,200	321,000	4,240
1,650	1,650	150	〃	333,100	406,400	385,800	4,990
1,800	1,800	160	〃	385,400	470,000	443,800	5,810
2,000	2,000	175	〃	448,700	547,100	520,800	7,050
2,200	2,200	190	〃	532,600	649,300	617,300	8,420
2,400	2,400	205	〃	別途見積			9,990
2,600	2,600	220	〃				11,500
2,800	2,800	235	〃				13,200
3,000	3,000	250	〃				15,100